power 2400 mono power amplifier




The **power2400** mono block power amplifier offers outstanding audio performance with dependability. Its transparency and astounding levels of resolution make it ideal for critical monitoring applications especially in partnership with any one of the PMC three-way passive monitors.

This British, hand built, 3U rack mount amplifier produces a commanding 1200W into 8 ohms with a flat frequency curve under all loads. Its intelligent single feedback loop circuit senses the loudspeaker's load and adjusts the response accordingly and creates an extremely low output impedance. With this in mind you are not only guaranteed a highly accurate balance but also remarkable dynamics and control over all the monitor's drivers.

Both power supply and amplifier are highly efficient with the amplifier delivering 84% efficiency reducing current usage

and both exhibit extremely low radiated and conducted EMI - perfect for low noise environments. Globetrotting presents no problem as the mains input is switchable from 115V or 230V-240V with the output connections via substantial binding posts and audio input is via a high quality Neutrik, XLR socket.









Specifications

Power output @1%THD 1200W into 8Ω

2400W into 4Ω

THD+N 0.008% at 1kHz, 10W, into 8Ω

THD+N typical 0.013% at 20Hz - 20kHz, 10W into 8Ω

Frequency response 10Hz - 50kHz -3dB

Damping factor 160 (20Hz - 20kHz) ref 8Ω

Input impedance $100k\Omega$ Voltage gain34dB

Sensitivity 1.95Vrms for rated output power

Heat dissipation1100BTU per hour at $1/8^{th}$ rated power into 8Ω Dynamic range119dB relative to rated output power into 8Ω Mains connectionIEC C20 3 pole - 115v or 230-240v (switchable)

Power consumption 60W - idle

Dimensions H 133mm x W 482mm x D 470mm

Weight 14.5kg

subject to change without notice

